

# PTFE Coated Fiberglass Part Numbers

**15T**

**55 -**

**190**

**3**

**WHT**

**Coating Percentage**  
(nominal)

12T 12% PTFE  
15T 15% PTFE

**Coating Type**

01. Unsinterd, Natural  
04. Sintered, Natural  
25. Nomex  
51. Unsintered, Natural.,  
Blk, Brwn  
52. Sintered,heat cleaned  
colors  
54. Sintered, Natural,  
BLK, BRN  
55. Unsintered, heat  
cleaned colors or white

**Yarn Size**

-032 150 2/2  
-043 150 1/3  
-064 150 1/2  
-096 225 1/2  
-190 450 1/2

**Number of Ends Up:**

X = 7005 tube:  
(1 end bulk)  
Braider Tubes:  
1, 2, 3, 4,  
5, 6, 7, 8 ends.

**Color:**

NAT = Natural WHT = White  
BLU = Blue GRN = Green  
RED = Red YLW=Yellow  
BLK = Black BRN= Brown  
GRY = Gray VLT= Violet  
ORG = Orange

**Example: 15T55-1903WHT.**

\* 15% PTFE coating / unsintered, heat cleaned  
450 1/2, packaged 3 ends on a braider tube, white.

## Braider Packages Available

Package Descr.	# ends (type)	approx. wt. per tube (lbs)	Inside Dia.(in)	Length (inches)	Max OD (inches)
Pkg #47 Braider bobbin	1-10	1/3 lb	5/8"	4 1/4"	2"
Pkg #4035 Braider bobbin	1 - 10	1/2 lb	5/8"	5 1/4"	2"

Other packages are available for certain yarns. Please contact the factory for details.  
All values subject to change without notice.

**W.F. Lake Corp.**  
P.O. Box 4214  
65 Park Road  
Glens Falls, NY 12804  
Customer Service: (800) 428-1162  
Tel: (518) 798-9934  
Fax: (518) 798-9936

[www.wflake.com](http://www.wflake.com)



## Standards / Specifications:

Mil-STD-1285  
High Temp.: Mil-W-7139  
Munsell ANSI/EIA-359-A  
Mil Std- 104



**W.F. LAKE**

High Performance PTFE & Silicone Coated Products